Model Number 377A14	PRECISION CONDENSER MICROPHONE								sion: E I #: 45005	
Performance		<b>ENGLISH</b>	<u>SI</u>		OPTIONAL VERSIONS					
Nominal Microphone Diameter		1/4"	1/4"		Optional versions have ident					
Frequency Response Characteristic		Pressure	Pressure		except where	re noted bel	ow. More than one	e option may be use	d.	
Open Circuit Sensitivity		1.0 mV/Pa	1.0 mV/Pa	[3]						
Open Circuit Sensitivity(± 3 dB)		-60 dB re 1 V/Pa	-60 dB re 1 V/Pa	[3]						
Frequency Range(± 2 dB)		4 to 70,000 Hz	4 to 70,000 Hz							
Lower Limiting Frequency(-3 dB)		0.25 to 3.0 Hz	0.25 to 3 Hz							
Resonant Frequency(90° Phase Shift)		65,000 Hz	65,000 Hz	[1]						
Inherent Noise		<35 dB(A) re 20	<35 dB(A) re 20							
		μPa	μPa							
Dynamic Range(3% Distortion Limit)  Environmental		178 dB re 20 μPa	178 dB re 20 μPa	[1]	NOTES:					
Temperature Range(Operating)		-40 to +248 °F	-40 to +120 °C		[1] Typical.					
Temperature Coefficient of Sensitivity(+14 to +122°F (-10 to +50°C))		0.004 dB/°F	0.007 dB/°C	[1][3]	[2] Prepolarized					
Static Pressure Coefficient		-0.003 dB/kPa	-0.003 dB/kPa	[1][3]	[3] re 250 Hz					
Humidity Coefficient of Sensitivity(0 to 100%, non-condensing)		± 0.0012 dB/%RH	± 0.0012 dB/%RH	[3]						
Influence of Axial Vibration (0.1q (1 m/s²))		66 dB re 20 uPa	66 dB re 20 µPa	[1]						
Electrical		00 ав те 20 рг а	00 dB le 20 μl a	1.1						
Capacitance(Polarized)		5 pF	5 pF	[1]						
Polarization Voltage		0 V	0 V	[2]						
Physical					SUPPLIED ACCESSORIES:					
Housing Material		Stainless Alloy	Stainless Alloy		Model ACS-20 Calibration of	Model ACS-20 Calibration of Precision Condensor Microphones (1)				
Venting		Side	Side							
Mounting Thread(Preamp	plifier)	0.2244 - 60 UNS	5.7 mm - 60 UNS		L					
Mounting Thread(Grid)		0.25 - 60 UNS	6.35 mm - 60 UNS		Entered: LK Engineer:	: MT - 5	Sales: MV	Approved: MT	Spec Number:	
Size (Diameter x Height)	(with grid)	0.28 in x 0.41 in	7.0 mm x 10.5 mm		Date: 10/13/2016 Date: 10/	/42/2046 [	Doto: 40/42/2046	Date: 10/13/2016	54344	
Size (Diameter x Height)	(without grid)	0.25 in x 0.36 in	6.4 mm x 9.1 mm		Date: 10/13/2016 Date: 10/	13/2016 L	Date: 10/13/2016	Date: 10/13/2016	0-10-1-1	
Weight		0.06 oz	1.8 gm	[1]						
All specifications are at room temperature unless otherwise specified.  In the interest of constant product improvement, we reserve the right to change specifications without notice.					<b>PCB</b> PIEZUTRUNICS Fa				one: 716-684-0001 x: 716-684-0987	
$ICP^{ ext{@}}$ is a registered trademark of PCB Group, Inc.								84-0987 o@pcb.com		



Represented in India by

Structural Solutions Pvt Ltd. | Phone: 040 2322 2380 | Email: sales@stsols.com

#4th Floor, Sudheer Tapani Towers, Himayath Nagar, Hyderabad - 500 029