

Model Number EX607A11	HAZARDOUS AREA APPROVED INDUSTRIAL ICP® ACCELEROMETER		Revision H ECN #: 26068
Performance	ENGLISH	SI	Optional Versions (Optional versions have identical specifications and accessories as listed for standard model except where noted below. More than one option maybe used.) M - Metric Mount Supplied Accessory: Model M080A159 Mounting stud, 1/2-20 to M6x1 (for Models M607A11 and M607A61) replaces Model 080A156 Notes [1] Typical. [2] Conversion Factor 1g = 9.81 m/s ² . [3] Zero-based, least-squares, straight line method. [4] Measured with mounting stud. [5] 1/4-28 has no equivalent in S.I. units. [6] Stud torque must exceed sensor hex nut torque to ensure proper dismantling. [7] 1/8" hex Allen key required for English version, 4 mm hex Allen key required for Metric version. [8] Twisted shielded pair. [9] See PCB Declaration of Conformance PS023 or PS060 for details. Supplied Accessories 080A156 Mounting Base (1) ICS-2 NIST-traceable single-axis single-point amplitude response calibration at 6000 cpm (100 Hz) (1)
Sensitivity (±15 %)	100 mV/g	10.2 mV/(m/s ²)	
Measurement Range	±50 g	±490 m/s ²	
Frequency Range (±3 dB)	30 to 600000 cpm	0.5 to 10000 Hz	
Resonant Frequency	1500 kcpm	25 kHz	
Broadband Resolution (1 to 10000 Hz)	350 µg	3434 µm/sec ²	
Non-Linearity	±1 %	±1 %	
Transverse Sensitivity	≤7 %	≤7 %	
Environmental			
Overload Limit (Shock)	5000 g pk	49050 m/s ² pk	
Temperature Range	-65 to +250 °F	-54 to +121 °C	
Enclosure Rating	IP68	IP68	
Hazardous Area Approval	Ex ia IIC T4, AExia IIC, T4	Ex ia IIC T4, AExia IIC, T4	
Hazardous Area Approval	EEx nL IIC T4, -40°C≤Ta≤121°C, II 1 G	EEx nL IIC T4, -40°C≤Ta≤121°C, II 1 G	
Hazardous Area Approval	CI I, Div I, Groups A, B, C, D; CI II, Div I, Groups E, F, G; CI III, Div I	CI I, Div I, Groups A, B, C, D; CI II, Div I, Groups E, F, G; CI III, Div I	
Hazardous Area Approval	CI I, Div 2, Groups A, B, C, D; ExnL IIC T4, AExnA IIC T4	CI I, Div 2, Groups A, B, C, D; ExnL IIC T4, AExnA IIC T4	
Hazardous Area Approval	EEx nL IIC T4, -40°C≤Ta≤121°C, II 3 G	EEx nL IIC T4, -40°C≤Ta≤121°C, II 3 G	
Electrical			
Settling Time (within 1% of bias)	≤2 sec	≤2 sec	
Discharge Time Constant	≥0.3 sec	≥0.3 sec	
Excitation Voltage	18 to 28 VDC	18 to 28 VDC	
Constant Current Excitation	2 to 20 mA	2 to 20 mA	
Output Impedance	<150 Ohm	<150 Ohm	
Output Bias Voltage	8 to 12 VDC	8 to 12 VDC	
Spectral Noise (10 Hz)	8 µg/√Hz	78.5 (µm/sec ²)/√Hz	
Spectral Noise (100 Hz)	5 µg/√Hz	49.1 (µm/sec ²)/√Hz	
Spectral Noise (1 kHz)	4 µg/√Hz	39.2 (µm/sec ²)/√Hz	
Electrical Isolation (Case)	>10 ⁸ Ohm	>10 ⁸ Ohm	
Physical			
Size (Hex x Height)	9/16 in x 0.97 in	14 mm x 24.6 mm	
Weight (without cable)	1.1 oz	31 gm	
Mounting	Stud	Stud	
Mounting Thread	1/4-28 Male	1/4-28 Male	
Mounting Torque (stud)	7 to 8 ft-lb	9.5 to 10.8 Nm	
Mounting Torque (hex nut)	2 to 5 ft-lb	2.7 to 6.8 Nm	
Sensing Element	Ceramic	Ceramic	
Sensing Geometry	Shear	Shear	
Housing Material	Stainless Steel	Stainless Steel	
Sealing	Welded Hermetic	Welded Hermetic	
Electrical Connector	Molded Integral	Molded Integral	
	Cable	Cable	
Electrical Connection Position	Side	Side	
Cable Length	10 ft	3.0 m	
Cable Type	Polyurethane	Polyurethane	

Entered: NJF	Engineer: EGY	Sales: NJF	Spec Number:
Date: 03/21/2007	Date: 03/21/2007	Date: 03/21/2007	12650



3425 Walden Avenue
 Depew, NY 14043
 UNITED STATES
 Phone: 716-684-0003
 Fax: 716-684-3823
 E-mail: imi@pcb.com
 Web site: www.imi-sensors.com



All specifications are at room temperature unless otherwise specified.

In the interest of constant product improvement, we reserve the right to change specifications without notice.

ICP® is a registered trademark of PCB group, Inc.

